

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A method comprising:
 - (a) calculating estimated weights for identified errors in recognition of utterances;
 - (b) marking sections of the utterances as being misrecognized and associating the ~~corresponding~~ estimated weights with the ~~these~~ sections of the utterances; and
 - (c) using the weighted sections of the utterances to convert a speaker independent model to a speaker dependent model.
2. (original) The method of claim 1, wherein parts (a) – (c) are repeated at least once.
3. (original) The method of claim 1, wherein the utterances are converted into a recognized phone string a first time through applying the speaker independent model and thereafter through applying the most recently obtained speaker dependent model.
4. (currently amended) The method of claim 1, wherein calculating the estimated weights ~~comprises are computed through~~ computing an average likelihood difference per frame and then computing a weight value by averaging the average likelihood difference over ~~all the~~ error words.
5. (currently amended) The method of claim 1, wherein calculating the estimated weights comprises computing an average likelihood difference per frame ~~is used to calculate the estimated weights and is computed~~ according to the equation (1) as follows:

$$L_n = \frac{H_L^n}{H_e^n - H_b^n} - \frac{R_L^n}{R_e^n - R_b^n} \quad (1),$$

where H_L^n is ~~a~~ the log likelihood of hypothesis word n, H_b^n is ~~a~~ the beginning frame index (in time), and H_e^n is ~~an~~ the end frame index, and R_L^n , R_b^n and R_e^n are counter parts for a reference string.

6. (currently amended) The method of claim 5, wherein calculating the estimated weights further comprising a ~~the~~ weight for misrecognized words of a particular speaker "i" is ~~calculated~~ according to equation (2) as follows:

$$W_i = \frac{1}{m} * \sum_{n=1}^m |L_n| \quad (2), \text{ wherein } m$$

is a number of misrecognized words.

7. (currently amended) The method of claim 1, wherein for a particular speaker, different misrecognized words ~~may~~ have ~~[[a]]~~ different weights ~~weight~~.

8. (currently amended) A method comprising:

(a) recognizing utterances through converting the utterances into a recognized ~~phone~~ string;

(b) comparing the recognized ~~phone~~ string with a reference ~~phone~~ string to determine errors;

(c) calculating estimated weights for sections of the utterances;

(d) marking the errors in the utterances and providing corresponding estimated weights to form adaptation enrollment data; and

(e) using the adaptation enrollment data to convert a speaker independent model to a speaker dependent model.

9. (currently amended) The method of claim 8, wherein the utterances are converted into the recognized ~~phone~~ string through applying the speaker independent model.

10. (original) The method of claim 8, wherein parts (b) – (e) are repeated until differences between the reference and recognized strings are less than a threshold.

11. (currently amended) The method of claim 8, wherein the utterances are converted into a recognized ~~phone~~ string a first time through applying the speaker independent model and thereafter through applying the most recently obtained speaker dependent model.

12. (currently amended) The method of claim 8, wherein calculating the estimated weights comprises ~~are computed through~~ computing an average likelihood difference per frame and then computing a weight value by averaging the average likelihood difference over all ~~the~~ error words.

13. (currently amended) The method of claim 8, wherein calculating the estimated wieights comprises calculating an average likelihood difference per frame ~~is used to calculate the estimated weights and is calculated~~ according to the equation (1) as follows:

$$L_n = \frac{H_L^n}{H_e^n - H_b^n} - \frac{R_L^n}{R_e^n - R_b^n} \quad (1),$$

where H_L^n is ~~a the~~ log likelihood of hypothesis word n, H_b^n is ~~a the~~ beginning frame index (in time), and H_e^n is ~~an the~~ end frame index, and R_L^n , R_b^n and R_e^n are counter parts for the reference string.

14. (currently amended) The method of claim 13, wherein calculating the estimated weights comprises calculating a the weight for misrecognized words of a particular speaker "i" is calculated according to equation (2) as follows:

$$W_i = \frac{1}{m} * \sum_{n=1}^m |L_n| \quad (2), \text{ wherein } m$$

is a number of misrecognized words.

15. (currently amended) The method of claim 8, wherein for a particular speaker, different misrecognized words ~~may~~ have ~~[[a]]~~ different weights ~~weight~~.

16. (currently amended) An article of manufacture ~~A memory~~ comprising:

a storage medium having instructions thereon which when executed cause a processor computer system to perform operations comprising the following method:

- (a) calculating estimated weights for identified errors in recognition of utterances;
- (b) marking sections of the utterances as being misrecognized and associating the ~~corresponding~~ estimated weights with the ~~these~~ sections of the utterances; and
- (c) using the weighted sections of the utterances to convert a speaker independent model to a speaker dependent model.

17. (currently amended) The article of manufacture method of claim 16, wherein parts (a) – (c) are repeated at least once.

18. (currently amended) The article of manufacture method of claim 16, wherein the utterances are converted into a recognized phone string a first time through applying the speaker independent model and thereafter through applying the most recently obtained speaker dependent model.

19. (currently amended) The article of manufacture method of claim 16, wherein the estimated weights are computed through computing an average likelihood difference per frame and then computing a weight value by averaging the average likelihood difference over ~~all the~~ error words.

20. (currently amended) The article of manufacture method of claim 16, wherein an average likelihood difference per frame is used to calculate the estimated weights and is computed according to ~~the~~ equation (1) as follows:

$$L_n = \frac{H_L^n}{H_e^n - H_b^n} - \frac{R_L^n}{R_e^n - R_b^n} \quad (1),$$

where H_L^n is ~~a the~~ log likelihood of hypothesis word n, H_b^n is ~~a the~~ beginning frame index (in time), and H_e^n is ~~an the~~ end frame index, and R_L^n , R_b^n and R_e^n are counter parts for a reference string.

21. (currently amended) The article of manufacture ~~method~~ of claim 20, wherein a ~~the~~ weight for misrecognized words of a particular speaker "i" is calculated according to equation (2) as follows:

$$W_i = \frac{1}{m} * \sum_{n=1}^m |L_n| \quad (2), \text{ wherein } m$$

a number of misrecognized words.

22. (currently amended) The article of manufacture ~~method~~ of claim 16, wherein for a particular speaker, different misrecognized words ~~may~~ have ~~[[a]]~~ different weights ~~weight~~.

23. (currently amended) An article of manufacture ~~A memory~~ comprising:
a storage medium having instructions thereon which when executed cause a processor
~~computer system~~ to perform operations comprising the following method:

- (a) recognizing utterances through converting the utterances into a recognized phone string;
- (b) comparing the recognized ~~phone~~ string with a reference ~~phone~~ string to determine errors;
- (c) calculating estimated weights for sections of the utterances;
- (d) marking the errors in the utterances and providing corresponding estimated weights to form adaptation enrollment data; and
- (e) using the adaptation enrollment data to convert a speaker independent model to a speaker dependent model.

24. (currently amended) The article of manufacture ~~method~~ of claim 23, wherein the utterances are converted into the recognized ~~phone~~ string through applying the speaker independent model.

25. (original) The article of manufacture ~~method~~ of claim 23, wherein parts (b) – (e) are repeated until differences between the reference and recognized strings are less than a threshold.

26. (currently amended) The article of manufacture method of claim 23, wherein the utterances are converted into a recognized ~~phone~~ string a first time through applying the speaker independent model and thereafter through applying the most recently obtained speaker dependent model.

27. (currently amended) The article of manufacture method of claim 23, wherein the estimated weights are computed through computing an average likelihood difference per frame and then computing a weight value by averaging the average likelihood difference over ~~all the~~ error words.

28. (currently amended) The article of manufacture method of claim 23, wherein an average likelihood difference per frame is used to calculate the estimated weights and is calculated according to the equation (1) as follows:

$$L_n = \frac{H_L^n}{H_e^n - H_b^n} - \frac{R_L^n}{R_e^n - R_b^n} \quad (1),$$

where H_L^n is ~~a the~~ log likelihood of hypothesis word n, H_b^n is ~~a the~~ beginning frame index (in time), and H_e^n is ~~a the~~ end frame index, and R_L^n , R_b^n and R_e^n are counter parts for the reference string.

29. (currently amended) The article of manufacture method of claim 28, wherein ~~a the~~ weight for misrecognized words of a particular speaker "i" is calculated according to equation (2) as follows:

$$W_i = \frac{1}{m} * \sum_{n=1}^m |L_n| \quad (2), \text{ wherein } m$$

~~is~~ a number of misrecognized words.

30. (original) The article of manufacture method of claim 23, wherein for a particular speaker, different misrecognized words ~~may~~ have ~~[[a]]~~ different weights ~~weight~~.